


Step 1:

Place the wall wizard on its side on the template at the bottom of the page, with the top block over the top block of the template so it covers the template block.

Then adjust the blocks by using the 10mm open end spanner to adjust the distance between the top block and bottom block, to the left anticlockwise the blocks will spread apart, to the right clockwise they will retract.

To start; turn the hex drive shaft to the left anticlockwise with the spanner so the blocks spread apart, when there is a gap of about 15mm between the blocks you can then use your fingers to spread the blocks apart keeping your fingers on the top block and turn with your other fingers to match the template.

The inside distance between the top block jaw tongue and the bottom block jaw tongue need to be a distance of about 78mm so both jaw tongues fit over the brick edge and into the raked out cavity, the cavity needs to be no less than 9mm deep and 8mm high.



Step 3:

Turn the hex drive shaft until the top and bottom jaw tongues contact the top and bottom ledge of the brick, then turn the drive shaft about haft a turn until the blocks are locked firmly onto the brick so that you cannot pull the wall wizard off the brick by hand try not to over tighten the jaw blocks.

Your Wall Wizard is now ready to use.



Step 2:

Push the wall wizard jaw tongues into the brick cavity so the back of the block face is on the brick face so there is no gap between the blocks and the brick. If there is a gap then the brick mortar needs to be scraped out with the mortar rake on the spanner tool, so the back of the block is flush on the brick. Make sure there are no mortar lumps under the wall wizard tongue top and bottom if there is it needs

← Mortar rake

Measure -



to be scraped off.

Make sure you place the block jaw tongues onto a solid smooth flat brick ledge, do not place onto rough cracked or decaying bricks.

Once the blocks are place flush onto the brick, hold the blocks onto the brick with one hand then use the 10mm open end spanner to turn the hex drive shaft to the right clockwise, the block jaws will then tighten onto the brick.






Instructions for attaching a wall planter to the Wall Wizard

Measure the distance between the keyhole mounting slots on the wall pot minus 4mm for pot clips. Then attach a wall wizard to a brick on the wall, this will be the left-hand side wall wizard. Attach the other wall wizard to the wall with finger pressure tightness only.

Then measure the same distance from outside edge on the left block to the out side edge of the right block. See illustration right.

Not to be used for half round wall pots deeper than 165mm from the back of the wall pot to the outside edge of the wall pot, and 150mm for wall troughs.



When your Wall Wizard is extended to attach to a brick it should fit this template.


Attach the left-hand planter holding clip to the wall wizard according to the illustrations to the right. Then attach the right-hand clip to the wall wizard to the right the same way.

See illustration to right and below.





Place the top of the planter clip into the slot on the top block at a right angle to the block face, then rotate the clip down so it clips under the block as in the illustrations 1, 2, 3.





Fill your wall planter with potting mix and plants before mounting on a wall. Place the wall planter with plants onto the clip hooks, make sure you position your wall planter out of the reach of children.

Your wall planter is now ready to enjoy.

WALL WIZARD

Adjustable Wall mounting System

Design for standard brick sizes 65mm to 76mm high the cavity gap between the bricks is to be no less than 8mm high and 9mm deep.







NO need to drill holes In Bricks Exterior:

Easy to attach to a brick Attaches in seconds Adjusting spanner supplied with built-in mortar rake.

The Wall Wizard is designed to make it easy to hang articles on a brick wall without the need to drill holes in the bricks. It simply attaches securely to a brick in seconds. (Great for rented properties)

Wall Wizard is adjustable with the 10mm open end spanner and mortar rake provided.

Instructions for attaching Wall Wizard are on reverse.

Instructions for attaching Wall Wizard are on reverse side.

Supports articles such as:

Wall Planters, Pictures, Posters, Mirrors, Plaques, Wall Ornaments, Christmas lights & Decorations etc. Each Wall Wizard holds up to 6kg single no hooks. Wall Wizard with stainless steel clip hook holes 3kg. Two Wall Wizards with clips hooks holds 6kg wall pot.









For more information about products and where to buy go to www.ihgp.com.au

Innovative Home and Garden Products Australian Owned & Made

Patented Product:

Disclaimer: To the full extent permitted by law, any warranties, conditions, guarantees or representation about the state, quality or fitness for purpose of the Wall Wizard are hereby negatived.

The liability of Innovative Home and Garden Products ("IHGP") in respect of any breach of a warranty or conduction that cannot be excluded, is limited, at IHGP's discretion to the replacement or repair of the product. This product is to be installed and used according to the instructions provided with the product and not in any other way. The customer agrees to indemnify and hold indemnified IHGP against all claims for damages to persons or property arising out of the installation or use of the product not in accordance with the instructions provided.